



340
Union taper seat, ISO/EN U11

Torque and notes for installation please find in "Technical Product Notes".
374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
* Inside hexagon
** Version

EN	Dim.	** 374 G	Black	Galvanised	a	z1	s1	s2	s3
	(inch)	(inch)	Code	Code	(mm)	(mm)	(mm)	(mm)	(mm)
•	1/6	1/2	770 340 101	770 340 201	38	24	15	26	15
•	1/4	5/8	770 340 102	770 340 202	42	22	19	28	*10
•	3/8	3/4	770 340 103	770 340 203	48	28	22	32	*12
•	1/2	1	770 340 104	770 340 204	48	22	26	41	25
•	1/2	s 1 1/8	770 340 120	770 340 220	48	22	26	44	26
•	3/4	1 1/4	770 340 105	770 340 205	52	22	31	48	32
•	1	1 1/2	770 340 106	770 340 206	58	24	38	55	38
•	1 1/4	2	770 340 107	770 340 207	65	27	48	67	48
•	1 1/2	2 1/4	770 340 108	770 340 208	70	32	54	74	54
•	2	2 3/4	770 340 109	770 340 209	78	30	66	90	66
•	2 1/2	3 1/2	770 340 110	770 340 210	90	36	85	111	85
•	3	4	770 340 111	770 340 211	101	41	96	130	96
•	4	5	770 340 112	770 340 212	114	42	120	151	120